

# Fairisle

## Technical Specification

	CONSTRUCTION MACHINE GAUGE PILE HEIGHT TUFT DENSITY PILE WEIGHT	ISO 1766 ISO 1763	1/4th Loop Gauge 5.7 mm 42,779 Loops/m <sup>2</sup> 1,220 gms/m <sup>2</sup> 36 oz/yd <sup>2</sup>
	TOTAL CARPET WEIGHT CARPET THICKNESS WIDTH	ISO 8543 ISO 1765	2,676 gms/m <sup>2</sup> 9.8 mm 4 & 5 metre
	COMPOSITION PILE CONTENT PRIMARY BACKING SECONDARY BACKING	ISO 1833	100% Pure New Wool Woven Polypropylene Woven Secondary
	PERFORMANCE SUITABILITY WIRA ABRASION TEST STATIC LOADING DYNAMIC LOADING TUFT ANCHORAGE	ISO 10361 PD 6527:Clause 17 ISO 3416 ISO 2094 ISO 4919	Extra Heavy Domestic/Medium Contract Exceeds 14,300 Rubs 18.9% Thickness Loss after 24 hrs recovery 24.1% Thickness Loss after 1,000 impacts Above 1 kg
	COLOUR FASTNESS LIGHT FASTNESS WET FASTNESS SHAMPOO FASTNESS	ISO 105-B02 ISO 105-E01 ISO 18168	4/5 on all colours 4/5 on all colours 4/5 on all colours
	THERMAL VALUE TOG VALUE THERMAL RESISTANCE	ISO 5085-1	1.5 Tog 0.15m <sup>2</sup> k/w
	FLAMMABILITY CE MARK RATING HOT METAL NUT TEST METHENAMINE PILL TEST	CE BS 4790 ISO 6925	Cfl, S1 Pass - Low radius of ignition Pass
	CHEMICAL IMPACT FORMALDEHYDE	CE	E1
	BIOLOGICAL ATTACK MOTH / INSECT RESISTANT		Eulan Treated
	ANTI STATIC		0.3kv (Requirement less than +2.0kv)

## General Information

**INSTALLATION** - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

**MAINTENANCE** - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. Loop pile carpets can be vacuumed with cylinder vacuum cleaners using the suction attachment only. On upright vacuum cleaners lift the beater bar brush to avoid pile surface abrasion. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Occasionally wool may contain traces of the sheep's natural environment. These traces can be easily removed and do not effect the durability of the carpet. Joins in loop pile carpet can sometimes be visible, especially so in patterned loop pile. The use of seaming cement is advisable.

**MATCHING** - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

**IMPORTANT** - Minimum order length is 1.5 metres.