

PRIMO CHOICE

TECHNICAL SPECIFICATION



CONSTRUCTION

		SUPER	ELITE
MACHINE GAUGE		Tufted Cut Pile Carpet	Tufted Cut Pile Carpet
PILE HEIGHT	BS 4223/ISO 8543	1/10th Cut Pile	1/10th Cut Pile
TUFT DENSITY	BS 4223/ISO 8543	6.7 mm	8.6 mm
PILE WEIGHT	BS 4223/ISO 8543	139,500 tufts/m ²	162,750tufts/m ²
		1,152 gms/m ²	1,627 gms/m ²
		34oz/yd ²	48oz/yd ²
TOTAL CARPET WEIGHT	BS 4223/ISO 8543	1,899 gms/m ²	2,407gms/m ²
CARPET THICKNESS	BS 4051/ISO 1765	10.2mm	11.9mm
WIDTH	BS	4 & 5 metre	4 & 5 metre
ROLL SIZE		Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)	Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)

COMPOSITION



PILE CONTENT	BS 4407
PRIMARY BACKING	
SECONDARY BACKING	

100% Excelon Polypropylene
Woven Polypropylene
Woven Secondary

100% Excelon Polypropylene
Woven Polypropylene
Woven Secondary

PERFORMANCE



SUITABILITY	
WIRA ABRASION TEST	
STATIC LOADING	
DYNAMIC LOADING	
TUFT ANCHORAGE	

Heavy Domestic
Exceeds 50,000 Rubs
18% Thickness Loss after 24 hrs recovery
41.5% Thickness Loss after 1,000 impacts
Above 1kg

Extra Heavy Domestic / Medium Contract
Exceeds 50,000 Rubs
16.8% Thickness loss after 24 hrs recovery
31.3% Thickness loss after 1,000 impacts
Above 1kg

COLOUR FASTNESS



LIGHT FASTNESS	BS 1006
WET FASTNESS	BS 1006
SHAMPOO FASTNESS	BS 1006

4/5 on all colours
5 on all colours
5 on all colours

4/5 on all colours
5 on all colours
5 on all colours

THERMAL VALUE



TOG VALUE	BS 4745/ISO 5085-1
	1.0 Tog

1.2 Tog

FLAMMABILITY



METHENAMINE PILL TEST

CE

Pass - Low radius of ignition

Pass - Low radius of ignition

CHEMICAL IMPACT



FORMALDEHYDE

CE

E1

BIOLOGICAL ATTACK



MOTH / INSECT RESISTANT

Insect and Rot Proof

Insect and Rot Proof

GENERAL INFORMATION

Installation - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

Maintenance - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

Matching - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

Important - Minimum order length is 1.5 metres.