

# PRIMO GRANDE

## TECHNICAL SPECIFICATION



### CONSTRUCTION

MACHINE GAUGE	ISO 1766	1/10th Gauge Cut Pile
PILE HEIGHT	ISO 1763	11.4 mm
TUFT DENSITY		178,249 tufts/m <sup>2</sup>
PILE WEIGHT		1,966 gms/m <sup>2</sup>
TOTAL CARPET WEIGHT	ISO 8543	58 oz/yd <sup>2</sup>
CARPET THICKNESS	ISO 1765	2,903gms/m <sup>2</sup>
WIDTH		14.3 mm
		4 & 5 metre



### COMPOSITION

PILE CONTENT	ISO 1833	100% Excelon Polypropylene
PRIMARY BACKING		Woven Polypropylene
SECONDARY BACKING		Woven Secondary



### PERFORMANCE

SUITABILITY	PD 6527:Clause 17	Extra Heavy Domestic / Medium Contract
WIRA ABRASION TEST	ISO 3416	Exceeds 50,000 Rubs
STATIC LOADING	ISO 2094	20.1% Thickness loss after 24 hrs recovery
DYNAMIC LOADING	ISO 4919	28.7% Thickness loss after 1,000 impacts
TUFT ANCHORAGE		Above 1kg



### COLOUR FASTNESS

LIGHT FASTNESS	ISO 105-B02	3-4 on all colours
WET FASTNESS	ISO 105-E01	5 on all colours
SHAMPOO FASTNESS	BS 1006:UK-TB	5 on all colours



### THERMAL VALUE

TOG VALUE	ISO 5085-1	1.4 Tog
THERMAL RESISTANCE		0.14 m <sup>2</sup> k/w



### FLAMMABILITY

CE MARK RATING	CE	Efl
METHENAMINE PILL TEST	ISO 6925	Pass



### CHEMICAL IMPACT

FORMALDEHYDE	CE	E1
--------------	----	----



### BIOLOGICAL ATTACK

MOTH / INSECT RESISTANT		Insect & Rot Proof
-------------------------	--	--------------------



### ANTI STATIC

-0.1 kv (pass)

## GENERAL INFORMATION

**Installation** - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

**Maintenance** - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

**Matching** - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

**Important** - Minimum order length is 1.5 metres.