

Sensation

Technical Specification

CONSTRUCTION		ORIGINAL	ULTIMATE
MACHINE GAUGE		1/8th Gauge	1/8th Gauge
PILE HEIGHT	ISO 1766	12.7 mm	14.7 mm
TUFT DENSITY	ISO 1763	145,700 tufts/m ²	145,700 tufts/m ²
PILE WEIGHT		1,966 gms/m ²	2,305 gms/m ²
TOTAL CARPET WEIGHT	ISO 8543	58 oz/yd ²	68 oz/yd ²
CARPET THICKNESS	ISO 1765	2,903 gms/m ²	3,242 gms/m ²
WIDTH		14.9 mm	16.9 mm
		4 & 5 metre	4 & 5 metre
COMPOSITION		ISO 1833	100% Luxelle PP
PILE CONTENT			Woven Polypropylene
PRIMARY BACKING			Woven Secondary
SECONDARY BACKING			Woven Secondary
PERFORMANCE		ISO 10361	Extra Heavy Domestic / Medium Contract
SUITABILITY		PD 6527:Clause 17	Exceeds 50,000 Rubs
WIRA ABRASION TEST			23.4% Thickness Loss after 24 hrs recovery
STATIC LOADING	ISO 3416		28.8% Thickness Loss after 1,000 impacts
DYNAMIC LOADING	ISO 2094		27.7% Thickness Loss after 1,000 impacts
TUFT ANCHORAGE	ISO 4919		Above 1kg
COLOUR FASTNESS		ISO 105-B02	5 on all colours
LIGHT FASTNESS		ISO 105-E01	5 on all colours
WET FASTNESS		ISO 18168	5 on all colours
SHAMPOO FASTNESS			5 on all colours
THERMAL VALUE		ISO 5085-1	1.7 Tog 0.17 m ² k/w
TOG VALUE			2.2 Tog 0.2 m ² k/w
THERMAL RESISTANCE			
FLAMMABILITY		ISO 6925	Efl Pass
CE MARK RATING			Efl Pass
METHENAMINE PILL TEST			
CHEMICAL IMPACT		E1	E1
FORMALDEHYDE			
BIOLOGICAL ATTACK		Insect and rot proof	Insect and rot proof
MOTH / INSECT RESISTANT			
ANTI STATIC		0.0kv (Requirement less than +2.0kv)	0.0kv (Requirement less than +2.0kv)

General Information

INSTALLATION - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

MAINTENANCE - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

MATCHING - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

IMPORTANT - Minimum order length is 1.5 metres.